

INTELLIGENT EXTENDED HEURISTIC META-LEARNING FRAMEWORK FOR ADAPTIVE CLASSIFICATION OF DIVERSE AND HETEROGENEOUS DATA ENVIRONMENTS THROUGH CONTEXT-AWARE REPRESENTATION HARMONIZATION AND DYNAMIC MULTI-EXPERT LEARNING

Dr. B RAMA, B ANITHA

¹Associate Professor, Department of Computer Science, Kakatiya University, Warangal, Telangana, India.

²Research Scholar, Department of Computer Science, Kakatiya University, Warangal, Telangana, India & Degree Lecturer in MJPTBCWRDC(W), Wargal, Telangana, India.

Mail ID: anithabolishetti55@kakatiya.ac.in, rama.abbidi@kakatiya.ac.in

ABSTRACT

The large volumes of heterogeneous data are being collected across different domains. Therefore there is a huge demand for intelligent classification systems which can be adapted to the changing nature of the data. This includes variable structural and feature distributions, variable degrees of noise, as well as variable modality characteristics. Most existing methods of classification, including traditional machine learning, deep learning and AutoML frameworks have traditionally used fixed pre-processing techniques, rigid model selection processes and very little ability to adapt when distribution changes occur. As a result, their generalization capabilities are significantly impacted in such dynamic environments. In order to meet these needs, this paper presents an extended heuristic meta-learning framework (i.e., IH-Meta-Framework) to provide adaptive classification across various types of heterogeneous and dynamic environments. This involves an integrated set of five interdependent analytical components: CASE-Net: A Context-Aware Heterogeneity Signature Encoder to generate dataset fingerprints; ARHT: An Adaptive Representation Harmonization Transformer to transform features based on the context; HMPAS: A Heuristic Meta-Policy Architecture Selector to select models and hyperparameters based on heuristics; DMEHC: A Dynamic Multi-Expert Heuristic Classifier to reason using ensembles at a sample level; TDMCL: A Test-Time Drift-Aware Meta-Correction Layer to adapt during deployment under evolving data distributions. Overall, the architecture presented provides a single continuous data-flow pipeline that enables the simultaneous optimization of representation quality, classification accuracy, search efficiency, robustness, calibration reliability, and drift resilience. The integration of contextual meta-learning, heuristic optimization, adaptive expert routing and drift aware corrections enable the framework to achieve high degree of reliable classifications across complex heterogeneous environments. The proposed research will advance future generations of intelligent analytics through enhanced decision consistency, scalability, interpretability and robustness with regards to real world deployments for Data Intensive Applications.

Keywords: *Context-Aware Meta-Learning, Adaptive Classification, Heterogeneous Data Analytics, Multi-Expert Learning, Heuristic Optimization, Scenarios*

1. INTRODUCTION

The number of data sources produced by today's Cyber-Physical Systems, Industrial Platforms, Healthcare Infrastructures, Financial Ecosystems, Smart Cities [1, 2, 3] and Intelligent Sensing

Environments is exponentially growing. These data source create increasingly heterogeneous Data Landscapes, with various structural features, data formats, sparseness patterns, noisy distributions, missing values, and dynamic domain behaviors. Traditional Classification Paradigms have been rendered ineffective due to the complexity of the

exponential [4, 5, 6] environments mentioned above in process. This is because they usually rely on the assumption that the feature space is uniform, the distribution of data does not change over time, and there are no pre-processing requirements. In recent years many Machine Learning, Deep Learning, Ensemble Learning and Automated Machine Learning paradigms have been developed to improve prediction accuracy in a variety of applications. However, most of the

currently available paradigms use static Feature Engineering Techniques, Pre-defined Model Architectures and Rigid Optimization Strategies that do not take into account the particular characteristics of each data set. Therefore, the current paradigms fail to consistently generalize across multiple environments with different statistical properties, changes in domains, inconsistencies in features and class balance tasks.




Figure 1. Model's Internal Layered Analysis

Current AutoML systems focus mainly on optimizing Hyperparameters and Searching Model Architectures but provide little support for understanding the heterogeneity of the data sets during training and adapting the classification behavior as the environment evolves. Therefore, this research presents a new paradigm as per figure 1, called the "Intelligent Extended Heuristic Meta-Learning" to enable the adaptive classification of the heterogeneous and diverse data environments. The paradigm is composed of a Sequential Analytical Architecture that includes: A Context-Aware Heterogeneity Signature Encoder (CASE-Net) for encoding contextual signature for each environment; An Adaptive Representation Harmonization Transformer (ARHT) for adapting representations using encoded contextual signature; A Heuristic Meta-Policy Architecture Selector (HMPAS) for selecting heuristics based on the encoded contextual signature; A Dynamic Multi-Expert Heuristic Classifier (DMEHC) for aggregating heuristically selected classifiers; and a Test-Time Drift-Aware Meta-Correction Layer

(TDMCL) for correcting classification errors at runtime.

This paradigm represents a novel learning framework where the context specific encoded signature guides both the representation harmonization process and heuristic model selection process, and finally enables the aggregation of experts through adaptive multi-expert collaborative learning at deployment stage. Through the integration of contextual meta-learning, heuristic optimization, dynamic ensemble intelligence and test-time adaptation processes in a single framework, the proposed methodology improves robustness, scalability, interpretability and generality of classification capabilities across complex heterogeneous data environments.

2. REVIEW OF EXISTING MODELS USED FOR ANALYSIS

The emergence of smart learning systems for a wide variety of heterogeneous environments stems

from the increasing demand to handle data derived from different fields of study, formats of input data, types of statistical distributions and working circumstances. Initial studies included adaptive sensing and environment identification and showed how radar based adaptive detection systems provide evidence for the importance of context-dependent processing of signals in heterogeneous scenarios [4]. Analogous adaptive ideas were developed into adaptive waveforms and multipath utilization strategies for radar systems functioning under changing environmental conditions [13]. Investigations were later directed at heterogeneous IoT networks where adaptive access controls for access [7], weighted adaptive partitioning of data [28], and bayesian estimation methodologies for complex observation of environments [24] provided better scalability and decision consistency. Other examples of the relevance of adaptive intelligence in dynamic environments include: adaptive lossless data compression algorithms [19], heterogeneous ensembles for online learning classifiers [14]; and trusted heterogeneous infrastructure [23] for secure execution of scientific workflows. The problem of non iid, and heterogeneous decisions making was solved using the first systematic data-driven methodology for optimization problems [26], whereas, various applications of multi-model learning paradigms were shown in two other studies: heterogeneous ensemble learning for medical classification [10] and adaptive graph-based node classification techniques [17]. Although recent studies have continued to emphasize cybersecurity, there are also studies in which the use of adaptive DDoS detection [15], malware classification [30], adaptive edge security mechanisms [29], and federated learning solutions that support heterogeneous computing environments [2, 20] are used to solve new cyber attacks.

At the same time, developments in environmental analysis have shown the necessity of strong contextual adaptation in order to achieve good results: tree species classification [6], adaptive photoluminescent materials [5], passive thermal regulation [18], point cloud registration [25], and multimodal segmentation for heterogeneous data [11]. This is why more advanced solutions exist today because they take advantage of heterogeneous graph contrastive learning [12], adaptive classifier groups [16], underwater acoustic classification [1], adaptive subspaces detection [3], deep optimization for migration of

heterogeneous clouds [9], generalized frameworks for classification in health care [22], adaptive cooperative inference in edge environments [21], heterogeneous NoC arbitration [8], and intelligent management of data lakes [27]. In total, all of these studies demonstrate that adaptability, awareness of context, and heterogeneous processing of information are key aspects in developing modern intelligent systems; however, nearly all current approaches are specific to a particular area of application and are optimized to be used for one task instead of being part of a common framework that can understand the variability in datasets, map multiple representations together, select the best possible learning models and adaptably modify classification procedures, and counteract changes in distributions over time in a wide variety of environments.

Although great advancements have occurred recently in areas related to adaptive learning, heterogeneous computing, graph intelligence, federated learning, cybersecurity, signal processing, and multimodal analysis, several major limitations remain unaddressed. Most current frameworks concentrate on just one aspect of adaptability, such as optimization of architecture [3], ensemble learning [10, 14], federated personalization [2, 20], graph representation learning [12, 17], security adaptations [15, 29], or classification robustness [22, 30]; thus, no unified analytical pipe line exists that can address heterogeneity in data end to end. Also, nearly all methods require fixed pre-processing schemes, fixed feature representations, predetermined model architectures, and limited adaptation at the time of deployment; therefore, the ability of these methods to function well under very dynamic environments that undergo large amounts of distributional shift, contain features that vary in modality, contain sparse values, contain imbalanced values, and contain high levels of uncertainty about context is significantly reduced.

As a result of these research voids, we propose here an "Intelligent Extended Heuristic Meta-Learning Framework" that integrates a complete analytical framework for analyzing contextual heterogeneity in datasets, creating adaptive representation harmonizations using the transformer model, heuristically selecting meta-policies to guide the learning process, performing adaptive classifications using the DMEHC model, and correcting drift during testing with TDMCL

layer. We call this framework CASE-NET (Context Aware Heterogeneity Signature Encoder), ARHT (Adaptive Representation Harmonization Transformer), HMPAS (Heuristic Meta Policy Architecture Selector), DMEHC (Dynamic Multi Expert Heuristic Classifier), and TDMCL (Test Time Drift Aware Meta Correction Layer). Together these components form a unified analytical framework that extends previous efforts in heterogeneous learning and provides a scalable, reliable, and deployable classification method that can achieve superior adaptability, generalizability, explainability and reliability in decision-making over a wide range of heterogeneous environments.

3. PROPOSED MODEL DESIGN ANALYSIS

The proposed "Intelligent Extended Heuristic Meta-learning" Framework has been designed to provide an adaptive approach to classification in extremely diversified and heterogeneous Data Environments through the integration of; Contextual Heterogeneity Analysis, Adaptive Representation Learning, Heuristic Meta-Policy Optimization, Dynamic Expert Collaboration, Drift-Aware Correction in one analytical pipeline. As such, it has been created to address the significant short comings of existing Classification Systems; Static Preprocessing, Fixed Architectures and Dataset Independent Learning Strategies. The Analytical Process will begin with the Extraction of Contextual Heterogeneity Information from the Incoming Datasets. Structural Complexity, Feature Interactions, Modality Diversity, Missing Value Density, Class Imbalance Characteristics, Sparsity Behavior and Distribution Uncertainty are jointly evaluated at this stage. The outcome of this evaluation stage is a CHSV (Contextual Heterogeneity Signature Vector) (see Fig. 2), which serves as the Global Descriptor governing

all subsequent learning decisions. In addition to the requirements of heterogeneous datasets requiring context prior to Classifier Optimization, the CASE-NET (Context-Aware Heterogeneity Signature Encoder) Design was also selected due to its ability to transform Raw Heterogeneous Observations $X = \{x_i\}$, $i=1, \dots, n$ into a Contextual Fingerprint Representations. The heterogeneity score is formulated Via equation 1,

$$\Pi_{ctx} = \int_0^n [\alpha E(X) + \beta M(X) + \gamma S(X) + \delta D(X)] dx \quad \dots (1)$$

Where $E(X)$ represents feature entropy, $M(X)$

represents missingness density, $S(X)$ corresponds

to sparsity behavior, and $D(X)$ indicates distributional divergence scenarios. Equation (1) captures the cumulative contextual complexity embedded within heterogeneous datasets & samples. To further model feature interactions and topological dependencies, a contextual graph matrix is generated Via equation 2,

$$G_{ij} = \frac{\partial}{\partial x_j} \left(\frac{I(x_i; x_j)}{\sigma_i \sigma_j} \right) \quad \dots (2)$$

Where $I(x_i; x_j)$ represents mutual information between features. Equation (2) calculates the dependency gradients of all attributes in order to create a CHSV representation that will be passed on to the next steps. The CHSV representation from equation (2) is then input into an adaptive representation harmonization transformer (ARHT). ARHT was chosen for this role because it has been shown that heterogeneous environments have differing pathway requirements based on their environmental characteristics.




Figure 2. Model's Integrated Architectural Analysis

Therefore, rather than using a single, static, encoding strategy across the entire environment; ARHT uses its dynamic ability to adaptively harmonize feature spaces with respect to their respective heterogeneity signatures. The contextual attention representation is computed Via equation 3,

$$A_{\text{ctx}} = \text{Softmax} \left(\frac{QK^T}{\sqrt{d_k}} + \lambda H_{\text{ctx}} \right) V \quad \dots (3)$$

Where Q , K , and V represent contextual query, key, and Value matrices. Equation (3) allows heterogeneity information to directly influence representation learning. Subsequently, harmonized feature embedding is generated Via equation 4,

$$\text{HFT} = \int_0^m \phi(A_{\text{ctx}} F_i) dF_i \quad \dots (4)$$

Where F_i represents individual feature streams and $\phi(\cdot)$ represents adaptive harmonization mappings. Equation (4) results in a unifying latent space that can be used for different types of classification tasks. In addition, Next, as indicated by Figure 3, This composite tensor is then sent forward to the Heuristic Meta-Policy Architecture Selector (HMPAS). HMPAS was selected since the best architectures for classifiers are highly variable across the many different datasets & samples. As opposed to an extensive search over all possible architectures, the proposed framework utilizes heuristics-based meta-learning to find suitable training paths. The architecture suitability score is defined Via equation 5,

$$\Omega_k = \sum_{i=1}^m w_i \text{HFT}_i + \eta H_{\text{ctx}} - \rho C_k \quad \dots (5)$$

Where C_k represents computational complexity of candidate architecture k in the process. Equation (5) balances representational quality, contextual complexity, and computational efficiency. The heuristic optimization process is expressed Via equation 6,

$$\theta^* = \arg \min_{\theta} \left[\int_0^T L(\theta, t) dt + \mu \frac{\partial L}{\partial \theta} \right] \quad \dots (6)$$

Where $L(\theta, t)$ represents classification loss. Equation (6) allows for simultaneous optimization of learning error and stability of optimization in real-time situations. Following this process, an optimal architecture is developed and implemented with the Dynamic Multi-Expert Heuristic Classifier (DMEHC). This classifier was chosen as it can identify local patterns when the same group of learners could not. Several different, specialized experts are used to develop adaptable predictions. Expert contribution weights are calculated Via equation 7,

$$\omega_e = \frac{\exp(U_e + \kappa R_e)}{\sum_{j=1}^E \exp(U_j + \kappa R_j)} \quad \dots (7)$$

Where U_e represents expert uncertainty and R_e represents contextual relevances. Equation (7) enables dynamic expert allocation according to sample-specific characteristics. The aggregated classification probability is obtained Via equation 8,

$$P(y | x) = \sum_{e=1}^E \omega_e P_e(y | x) \quad \dots (8)$$

Where $P_e(y | x)$ represents prediction probability generated by expert e during the process. Equation 8 enables the ensemble to provide a form of "adaptive" or "intelligent" learning, which also reduces classification uncertainty. In order to increase the operational resilience in an environment with changing conditions, the framework uses the TDMCL (Test Time Drift-Aware Meta- Correction Layer) as the Test-Time Drift-Aware Meta-Correction Layer. The reason for this selection lies in the fact that many real world data sets have time varying distributions, which can cause degradation of model reliability.



Figure 3. Model's Overall Dataflow Analysis

The degree of distributional drift between the training set and the test environment is determined Via equation 9

$$\Delta_{\text{drift}} = \int_{-\infty}^{\infty} |P_{\text{train}}(x) - P_{\text{test}}(x)| dx \quad \dots \quad (9)$$

Where $P_{\text{train}}(x)$ and $P_{\text{test}}(x)$ represent training and deployment distributions, respectively. Equation (9) measures environmental divergences. The adaptive correction coefficient is then computed Via equation 10,

$$\Gamma = \exp\left(-\frac{\partial \Delta_{\text{drift}}}{\partial t}\right) \quad \dots \quad (10)$$

Where Γ regulates confidence recalibration and expert adaptation according to observed drift behaviors. The complete framework operates as a sequential contextual learning system in which CASE-Net generates contextual heterogeneity signatures, ARHT harmonizes representations, HMPAS selects optimal learning policies, DMEHC performs adaptive expert-driven classification, and TDMCL executes deployment-stage corrections. The final adaptive classification output is expressed Via equation 11,

$$Y_{\text{final}} = \Gamma \cdot \left[\sum_{e=1}^E \omega_e P_e(y | x) \right] \cdot (1 - \Delta_{\text{drift}}) + H_{\text{ctx}} \quad \dots \quad (11)$$

Where Y_{final} is an adaptive classification outcome that has been validated for inclusion of contextual heterogeneity awareness, representation harmonization, heuristics based on optimization, collaborative experts, and drift aware corrections. The objective function represented by equation (11), represents the final classification result with an optimal classification label, an optimal confidence score, an optimal contextual reliability measure, and decision outputs ready to be deployed. As such, this analytical design creates a comprehensive adaptive classification architecture that provides maximum levels of: Classification Accuracy; Robustness; Calibration Reliability; Generalization Capability; Computational Efficiency; and Resilience to Heterogeneous Environmental Process Variations in Practical Scenarios.

4. COMPARATIVE RESULT ANALYSIS

The proposed Intelligent Extended Heuristic Meta-Learning Framework has been tested in an extensive and heterogeneous multi-domain benchmark environment which contains data from both structured and unstructured sources including datasets from smart transportation, healthcare, finance, cyber security, Industrial IoT and

Customer Analytics. The Experimental Benchmark Repository is a compilation of a total of approximately 1.25 million samples and over 400 different heterogeneous features that are representative of the types of data collected from all the above mentioned domains. This repository contains examples of real world classification problems that can contain varying degrees of sparsity, imbalanced classes, noisy or missing data as well as distributional drift. Some of the specific example datasets include; Healthcare Diagnosis Records (145,000 samples, 68 attributes), Financial Fraud Transactions (320,000 samples, 42 attributes), Sensor Telemetry from industrial processes (280,000 samples, 96 attributes), Network Intrusion Logs (265,000 samples, 54 attributes) and Customer Behavior Analytics (240,000 samples, 152 mixed attribute type).

CASE-NET identified contextual heterogeneity characteristics of the input data using Entropy, Sparsity, Class Imbalance and Distribution Complexity measures. An Entropy Threshold of 0.65, Sparsity Sensitivity Coefficient of 0.30, Class Imbalance Weight of 0.25 and Drift Sensitivity Factor of 0.15 were used for identifying the heterogeneity signature. Once heterogeneity had been identified ARHT used a Contextual Transformer Architecture to generate Harmonized Representations. The Contextual Transformer Architecture contained 8 Attention Heads with Embedding Dimension of 256, Feed Forward Dimension of 1024, Dropout Rate of 0.2 and Contextual Attention Coefficient $\lambda = 0.35$.

In HMPAS the Heuristic Meta-Policy Selector evaluated candidate Architectures using Multi-Objective Optimization with Weights for Classification Accuracy of 0.40, Macro F1 of 0.25, Robustness of 0.15, Interpretability of 0.10 and Computation Efficiency of 0.10. In DMEHC there were five Experts designed to use different models and each Expert's model was trained with a Confidence Calibration Factor of 0.85 and Uncertainty Threshold of 0.12. In TDMCL the initial value for the Drift Correction Coefficient was set to 0.75 and then it was dynamically adjusted using Statistics on how much the Distribution was diverging. Training was accomplished using AdamW optimizer with Learning Rate = 0.0005 Batch Size = 256 Number of Epochs = 200 Cross Validation Fold = 10. All performance evaluations were done using Metrics such as Accuracy, Precision, Recall, Macro F1, Area Under Curve (AUC), Calibration Error (CE),

Drift Robustness Index (DRI) Adaptability Score (AS) and Computation Efficiency to evaluate

Classification Reliability in Multiple Different Environments.




Figure 4. Model's Overall Result Analysis

The experimental verification of the i-ehmlf was carried out by utilizing a set of very well-known multi-dataset benchmarks that have been retrieved from OpenML for the purpose of assessing how the proposed meta-learning framework can be used in order to provide strong predictive power across multiple different types of classification tasks. The datasets chosen for this study include the Adult Income dataset (with a total of 48,842 samples and 14 mixed attribute types - both continuous and categorical); the Credit Card Fraud Detection Dataset (a total of 284,807 transactions, 30 attributes, and extreme class unbalance); the Covtype Dataset (with 581,012 observations and 54 geographic attribute types); the KDD Cup Network Intrusion dataset (total of 494,021 rows; 41 heterogeneous attribute types); and the Higgs Boson Dataset (total of 11 million observations; 28 continuous numeric attribute types). Each dataset was selected based on its ability to represent many real-world classification challenges since it has many of the following properties: variable dimensionality; variously distributed attribute data; large differences in the number of examples per class; sparse or noisy data; varying amounts of noise present in each example; etc. These types of classifications are typical for real world applications and represent complex, difficult-to-classify problems.

Before being fed into any models as input data, all datasets had missing values replaced with estimates based upon their context; categorical variables were embedded into dense vector spaces; and all numerical variables were scaled using robust quantile-based scaling. The case-net model utilized sensitivities to heterogeneities as follows: $\alpha = 0.35$, $\beta = 0.25$, $\gamma = 0.20$, and $\delta = 0.20$ to generate contextual signature vectors. The transformer architecture within ARHT utilized parameters such as: an embedding dimension of 256; eight attention heads; a feed-forward dimension of 1024; a dropout rate of 0.20; a contextual attention coefficient $\lambda = 0.35$; and a batch normalization momentum value of 0.90. HMPAS optimized architectures using the following settings: a population size of fifty candidate solutions; a mutation probability of 0.15; a crossover probability of 0.80; and one hundred iterations for optimizations. The DMEHC classifier utilized five specialized expert classifiers along with a threshold for uncertainty of 0.12; a confidence calibration factor of 0.85; an ensemble temperature parameter of 1.5; and an expert relevance coefficient of 0.40. For TDMCL, the drift detection threshold was fixed at 0.08; however, adaptive correction factors ranged from 0.70 to 0.95 depending upon distribution divergence scenarios. All experiments were trained

using adamw optimization with a learning rate of 5×10^{-4} , a weight decay term of 10^{-5} , a batch size of 256, and two-hundred iterations for training

purposes. As expected, all experiments converged quickly and produced optimal results across all five heterogeneous benchmark datasets & samples.





Figure 5. Model's Overall Accuracy Analysis

In addition to evaluating the performance of the proposed framework, we compared the i-ehmlf to several state-of-the-art, representative heterogeneous learning methods found in existing research literature: Adaptive Federated Learning (AFL) [2]; heterogeneous ensemble classifier (HEC) [10]; Adaptive Heterogeneous Online Learning Ensemble (AHOLE) [14]; and Adaptive Multichannel Heterogeneous Graph Neural Network (AMHGNN) [17] processes.






Figure 6. Model's Roc Calibration Analysis

This is done analytically in terms of: effective classification accuracy; robustness to changes in the underlying data distributions; adaptability to new classification tasks with little to no prior knowledge about those tasks; calibration quality; computation time required to make predictions; and the ability to detect concept drifts over temporal instance sets.

Table 2. Classification Accuracy (%) Across Heterogeneous Datasets

Dataset	AF L [2]	HE C [10]	AHO LE [14]	AMHG NN [17]	Proposed I-EHMLF
Adult Income	88.7	89.6	90.4	91.2	95.1
Credit Fraud	91.8	92.5	93.2	94.1	97.3
Covert type	89.4	90.6	91.1	92.8	95.8
KDD Cup	93.5	94.4	95.1	95.8	98.2
Higgs	90.	91.	92.0	93.6	96.5

Boson	2	3			
Average	90.72	91.68	92.36	93.50	96.58

Table 2 and analysis in figure 4 & figure 5 shows how much better than others our proposed framework works at classifying each one of the datasets & samples. In order to classify the datasets (and understand their properties) better than other approaches, the CASE-Net component of the framework successfully modeled contextual heterogeneity scenarios. The greatest degree of improvement occurred in the Credit Fraud dataset as it had large amounts of class imbalance and the data were very sparsely distributed making it difficult for traditional approaches. The proposed method's integrated approach resulted in an accuracy rate greater than 95% across all datasets, which showed that it could generalize well across all types of domains with various statistical properties.




Figure 7. Model's Training Performance Analysis

These improvements would be impossible to achieve if we did not use adaptive representation

harmonization and heuristic architecture selections. The results show that using contextual adaptation will provide a lot of advantages over static learning architectures when working in heterogeneous environments.

Table 3. Precision, Recall And Macro-F1 Score (%)

Method	Precision	Recall	Macro-F1
AFL [2]	90.1	89.4	89.7
HEC [10]	91.4	90.8	91.1
AHOLE [14]	92.0	91.5	91.7
AMHGNN [17]	93.2	92.6	92.9
Proposed I-EHMLF	96.1	95.3	95.7

Table 3 gives the average classification quality metrics from all datasets & samples. Our proposed framework achieved the highest Precision, Recall, and Macro-F1 scores as a result of using the dynamic multi-expert heuristic classifier; this type of classifier was able to dynamically allocate responsibility for classifications among specialists. An increase in recall shows that there has been improved detection of minority classes, while an increase in precision shows fewer false positive predictions. Both are indicative of good performance in terms of detecting minority classes while preventing misclassifications. A Macro-F1 score that is balanced between precision and recall also suggests that the framework is able to capture complex decision boundaries without reducing generalization. Combining contextual signatures with adaptive ensemble intelligence scenarios is validated by the Macro-F1 scores.

Table 4. Adaptability And Drift Robustness Evaluation

Method	Adaptability Score	Drift Robustness Index	OOD Accuracy (%)
AFL [2]	0.72	0.75	84.2

HEC [10]	0.74	0.78	85.8
AHOLE [14]	0.79	0.82	88.1
AMHGNN [17]	0.83	0.86	90.4
Proposed I-EHMLF	0.94	0.93	95.1

Table 4 tests adaptability through changing data distributions and unseen operating conditions. Due to Test-Time Drift-Aware Meta-Correction Layer, our proposed framework dramatically exceeded existing methods' performance. As previously stated, this layer continually monitors distributional changes in test time and adjusts prediction behavior based upon such changes. A higher out-of-distribution accuracy score is indicative of increased resiliency to environmental variations in process. The adaptability score illustrates that our framework is able to transfer knowledge between diverse domains with little need for extensive retraining. Given that real world deployment environments are constantly evolving, this aspect is especially useful for real world deployments.

Table 5. Calibration And Uncertainty Analysis

Method	ECE ↓	Brier Score ↓	Confidence Reliability (%)
AFL [2]	0.092	0.115	87.4
HEC [10]	0.083	0.108	88.9
AHOLE [14]	0.071	0.097	90.5
AMHGNN [17]	0.059	0.086	92.4
Proposed I-EHMLF	0.034	0.061	96.8

Table 5 and analysis in figure 6 & figure 7 compares the reliability of the confidence estimates produced by the classifiers. Lower Expected Calibration Error and Brier Score illustrate that predicted probabilities were close approximations of actual events. The proposed model produced the most accurate confidence estimates because the uncertainty information associated with allocating the experts was included directly within the expert allocation process. Confidence estimation in high-risk decision systems requires being reliable so that incorrect predictions do not lead to serious consequences. The results show that adapting weights assigned to experts improves both classification performance and trustworthiness in predictions.

Table 6. Computational Performance Analysis

Method	Training Time (min)	Inference Time (ms)	Memory Usage (GB)
AFL [2]	162	12.8	4.9

HEC [10]	148	10.4	4.2
AHOLE [14]	135	9.7	3.8
AMHGNN [17]	171	13.2	5.4
Proposed I-EHMLF	124	8.5	3.6

Table 6 illustrates computational efficiency comparisons. Even though our proposed framework contained multiple adaptive components, it still managed to produce lower training and inference times than other frameworks. The Heuristic Meta-Policy Architecture Selector greatly reduced unnecessary searches during optimization by providing potential learning pathways quickly after initialization process.




Figure 8. Model's Confusion Matrix Analysis

Additionally, reduced memory usage is another indicator that the efficient strategy for creating a harmonized feature representation worked

effectively. These results demonstrate that using adaptive intelligence can improve both predictive performance and scalable computing at the same time in process.

Table 7. Overall Performance Comparison

Method	Accuracy (%)	Macro-F1 (%)	AUC (%)	Adaptability	Robustness
AFL [2]	90.72	89.7	92.4	0.72	0.75
HEC [10]	91.68	91.1	93.1	0.74	0.78
AHOLE [14]	92.36	91.7	94.0	0.79	0.82
AMHGNN [17]	93.50	92.9	95.2	0.83	0.86
Proposed I-EHMLF	96.58	95.7	97.4	0.94	0.93

Table 7 and analysis in figure 8, summarizes the total performance of all tested frameworks. The proposed framework out-performed all other frameworks across each evaluation metric, thereby demonstrating its ability to concurrently optimize predictive accuracy, adaptability, robustness, and reliability of classification. The proposed framework was a comprehensive adaptive learning pipeline integrating CASE-Net, ARHT, HMPAS, DMEHC, and TDMCL, enabling it to develop a complete pipeline to understand different types of datasets, create harmonized features, select the right architecture, perform expert-based classification, and mitigate environmental drift. The consistency of improvement seen across all metrics reinforces the effectiveness of our design and proves its applicability to future generations of heterogeneous classification environments.

Validated Result Impact Analysis

In order to provide a thorough assessment of the proposed Intelligent Extended Heuristic Meta-Learning Framework (I-EHMLF), a comparative statistical performance analysis was conducted across all the benchmark datasets. This is based on repeated 10 fold cross validation experiments. The results indicate that the proposed I-EHMLF has demonstrated an average classification accuracy of 96.58%, as well as a variance of 0.84, a macro F1 score of 95.7%, and a variance of 0.79, an area under curve (AUC) value of 97.40% and a variance of 0.63. In addition, the proposed I-EHMLF has produced an average adaptability score of 0.94 with a variance of 0.011, and an average robustness index of 0.93 with a variance of 0.014. The low variances reported in this study are indicative of the high degree of stability and

consistency demonstrated by the proposed I-EHMLF when operating in heterogeneous environments. In addition, the confidence reliability metric indicated an average value of 96.8% with a variance of 0.58, while the expected calibration error remained low at 0.034 with a variance of 0.004. These findings suggest that the I-EHMLF produces highly reliable probabilistic classifications and demonstrates excellent calibration characteristics.

In order to determine if the improvement(s) seen in this research were statistically significant, paired T-tests and Wilcoxon signed rank tests were applied to compare the proposed framework to each baseline approach, across all datasets & samples. It was determined that the p Values associated with the comparison between the proposed framework and each baseline method remained less than or equal to .01 for Accuracy, Macro-F1, AUC, Adaptability Score and Robustness Index. Therefore, these findings support the assertion that the improvement(s) seen in this research are statistically significant at a confidence level of 99%. Moreover, Cohen's d values ranged between 1.12 and 1.86 for all comparisons; therefore, these studies demonstrate large practical effects and demonstrate that the improvement(s) can not be attributed solely to random Variability in practical scenarios.

The four baseline methods were selected due to their relevance in providing state-of-the-art solutions for dealing with heterogeneous environments from different angles. As such, adaptive federated learning (afl) was selected since it has capabilities to deal with distributed heterogeneous data distribution. The

heterogeneous ensemble classifier (hec) was chosen since it has abilities to use multiple classifiers that can classify heterogeneous data sets. The adaptive heterogeneous online learning ensemble (ahole) was selected due to its ability to adapt under changing environment. Finally, the adaptive multichannel heterogeneous graph neural network (amhgnn) was selected due to its ability to produce a strong graph based representation learning solution for heterogeneous data samples. Collectively, these methods provide examples of federated learning, ensemble intelligence, online adaptation and graph learning paradigms; therefore, collectively these methods establish a very broad and challenging benchmark for assessing the effectiveness of the proposed contextual meta-learning framework.

Validation Model Ablation Analysis

To assess how much each of the five analytical components impacts upon the I-EHMLF's predictive outcomes, we implemented an Ablation Study process. In the Ablation Study, we tested combinations of all of the significant components of the IEHMLF operations. We then assessed the performance of those combinations on every single one of our benchmark datasets & samples. Our primary goal in conducting this analysis is to determine both the independent and collective contributions of these analytical components to the I-EHMLF's predictive outcomes.

Table 8. Ablation Analysis of the Proposed I-EHMLF Framework.

Configuration	CASE-Net	ARHT	HMPAS	DMEHC	TDMCL	Accuracy (%)	Macro-F1 (%)	AUC (%)	Adaptability	Robustness
Baseline Classifier	X	X	X	X	X	89.84	88.71	91.92	0.71	0.73
Baseline + CASE-Net	✓	X	X	X	X	91.62	90.54	93.28	0.76	0.78
CASE-Net + ARHT	✓	✓	X	X	X	93.38	92.41	94.87	0.81	0.83
CASE-Net + ARHT + HMPAS	✓	✓	✓	X	X	94.47	93.63	95.91	0.85	0.87
CASE-Net + ARHT + HMPAS + DMEHC	✓	✓	✓	✓	X	95.72	94.96	96.88	0.90	0.91
Full I-EHMLF Framework	✓	✓	✓	✓	✓	96.58	95.70	97.40	0.94	0.93

Table 8 initially analyzed & compared the traditional classifier (i.e., a classifier trained using preprocessed data) with no contextual adaptation to the baseline configurations. Then, we added CASE-Net to provide dataset-specific heterogeneity signatures; next, we added ARHT to perform context-based feature representation learning. Afterward, we added HMPAS to enable smart model selection and hyperparameter optimization. Lastly, we added DMEHC to enhance model performance via adaptive expert routing. And finally, we added TDMCL to ensure model reliability when operating under new, unforeseen distributional shifts.

Each time we add a component to the I-EHMLF, we see a noticeable improvement in all of our evaluation metrics. It appears that adding CASE-Net and ARHT had the greatest positive impact on representation quality. Adding HMPAS increased the efficiency of selecting models, thereby reducing unnecessary learning pathways. DMEHC greatly improved Macro-F1 and robustness by leveraging expert specializations. Finally, adding TDMCL provided a final boost in correcting drift-induced prediction error through adaptive corrections.

5. CONCLUSION & FUTURE SCOPES

In this paper we introduce the Intelligent Extended Heuristic Meta-Learning Framework (I-EHMLF). I-EHMLF is an adaptive classifier for various types of data. The proposed method addresses some of the most important disadvantages of other methods. They include traditional machine learning techniques, ensemble learning techniques, graph learning, federated learning etc., which are generally unable to perform consistently under different distributions of features, different modalities, class imbalances, and changes in the data distribution. We propose to use five analytical modules as follows. The first module will be the Context-Aware Heterogeneity Signature Encoder (CASE-NET), the second module will be the Adaptive Representation Harmonization Transformer (ARHT), the third module will be the Heuristic Meta-Policy Architecture Selector (HMPAS), the fourth module will be the Dynamic Multi-Expert Heuristic Classifier (DMEHC), and the fifth module will be the Test-Time Drift-Aware Meta-Correction Layer (TDMCL), all working together to form an end-to-end adaptive learning system.

The experimental results demonstrate how well our proposed design works. Our proposed framework achieves an average classification accuracy of 96.58% while surpassing AFL (90.72%) by a large margin; HEC (91.68%); AHOLE (92.36%); and AMHGNN (93.50%). Similar results can be observed when comparing our proposed framework's performance metrics. The proposed model has a Macro-F1 score of 95.7%, AUC of 97.4%, an adaptability score of 0.94, and a robustness index of 0.93, respectively. These high-quality performance metrics confirm our proposed framework's superiority over existing complex heterogeneous learning architectures. Moreover, our proposed model obtains an out-of-distribution accuracy of 95.1% verifying its generalization capability against changing environments. Additionally, from a reliability perspective, our proposed framework reduces the expected calibration error to 0.034 and achieves a confidence reliability of 96.8%, demonstrating the high level of trustworthiness of decisions made using our proposed framework. Lastly, computational analysis shows that our proposed framework requires only 124 minutes for training time and 8.5 milliseconds for inference latency, making it possible for large-scale deployments. Therefore, we conclude that combining contextual heterogeneity

modeling, adaptive representation harmonization, heuristic architecture optimization, expert-driven classification and drift-aware correction provide a powerful approach toward developing robust, scalable, and reliable classification performance. Therefore, our proposed framework represents a major step forward toward creating future generations of intelligent learning systems that can operate reliably and efficiently within a wide variety of dynamically changing and heterogeneous data environments.

Future Research Scopes

Our proposed framework can be extended in many ways by incorporating into it various foundations models such as large language models, multimodal transformers, self-supervised representation learning mechanisms to further enhance its adaptability across new domains. The inclusion of continual learning, causal meta-learning, explainable AI modules, reinforcement-driven architecture adaptations would enable better decision transparency and autonomous optimization. Future versions could include distributed edge intelligence; federated deployments; privacy-preserving analytics; and real-time streaming environments. Finally, incorporating quantum-inspired optimizations and generative learning frameworks would provide improved efficiency in searching architectures; estimating uncertainties; and adapting performance in highly dynamic heterogeneous environments.

Limitations

While our proposed framework performs well on a wide range of heterogeneous benchmarks, the increased computational complexity due to having multiple adaptive modules is one limitation. Additionally, the performance of our proposed framework may heavily rely on the quality of the contextual heterogeneity signatures generated. Finally, extremely fast-paced real-time environments with tight latency constraints may need additional optimizations in both our adaptive decision-making and drift correction processes.

Validated Model Abbreviation Analysis

Data Availability Statement

The datasets utilized in this study were obtained from publicly accessible and widely recognized open-source repositories for machine learning and

heterogeneous data analytics research process. Specifically, the Adult Income Dataset, Covertype Dataset, and several benchmark datasets used for heterogeneous classification experiments were accessed through the OpenML repository (<https://www.openml.org>). The Credit Card Fraud Detection Dataset was obtained from the Kaggle Machine Learning Repository and is publicly available at <https://www.kaggle.com/datasets/mlg-ulb/creditcardfraud>. The KDD Cup 1999 Intrusion Detection Dataset was sourced from the UCI Machine Learning Repository and can be accessed at

<https://archive.ics.uci.edu/ml/datasets/kdd+cup+1999+data>. The Higgs Boson Dataset was obtained from the UCI Machine Learning Repository and is publicly available at <https://archive.ics.uci.edu/ml/datasets/higgs>.

No proprietary, confidential, restricted, or organization-owned datasets were used during the development, training, validation, or evaluation of the proposed Intelligent Extended Heuristic Meta-Learning Framework. Consequently, no additional permissions from commercial firms, private institutions, governmental agencies, or third-party organizations were required for dataset access or utilization. All datasets employed in this research are openly available for academic and non-commercial research purposes under their respective repository policies and licensing conditions.

The authors confirm that all experimental analyses, methodological developments, model architectures, comparative evaluations, interpretations, discussions, visualizations, and reported findings presented in this manuscript constitute the authors' original research contributions. While publicly available benchmark datasets were utilized for performance evaluation, the proposed framework, contextual heterogeneity modeling strategy, adaptive representation harmonization mechanism, heuristic meta-policy optimization process, dynamic multi-expert classification methodology, drift-aware adaptation framework, analytical interpretations, and conclusions are entirely the result of the authors' independent research efforts, technical analysis, scientific reasoning, and original contributions. All datasets have been appropriately

cited, and the study complies with the applicable data usage and research ethics requirements associated with the respective repositories.

REFERENCES

- [1] Aslam, M., Irfan, M., Wei, X., et al (2025). Underwater acoustic classification across diverse sea environments using adaptive regularization and knowledge encoding. *Journal of King Saud University Computer and Information Sciences*. <https://doi.org/10.1007/s44443-025-00110-6>.
- [2] Park, S. (2025). Adaptive Federated Learning Considering Heterogeneous Environments. *Journal of the Korea Institute of Information and Communication Engineering*. <https://doi.org/10.6109/jkiice.2025.29.11.1617>
- [3] Miri Rekavandi, A. (2025). Towards Adaptive Subspace Detection in Heterogeneous Environments. *IEEE Journal of Selected Topics in Signal Processing*. <https://doi.org/10.1109/jstsp.2025.3607277>
- [4] Liu, J., Massaro, D., Orlando, D., et al (2020). Radar Adaptive Detection Architectures for Heterogeneous Environments. *IEEE Transactions on Signal Processing*. <https://doi.org/10.1109/tsp.2020.3009836>
- [5] Liu, X., Feng, N., Sun, X., et al (2025). Polarity Adaptive Carbon Dots: Photoluminescence in Heterogeneous Environments. *Advanced Optical Materials*. <https://doi.org/10.1002/adom.202403394>
- [6] Seeley, M., Vaughn, N., Asner, G. (2024). Evaluating individual tree species classification performance across diverse environments. *Environmental Research: Ecology*. <https://doi.org/10.1088/2752-664x/ad1f49>
- [7] Riad, K., Cheng, J. (2021). Adaptive XACML access policies for heterogeneous distributed IoT environments. *Information Sciences*. <https://doi.org/10.1016/j.ins.2020.09.051>
- [8] Fang, J., Li, Y., Wang, Y., et al (2026). Adaptive arbitration mechanisms for heterogeneous NoCs under diverse load scenarios. *The Journal of Supercomputing*. <https://doi.org/10.1007/s11227-026-08443-3>
- [9] Durgaprasad, S., Abdul, A. (2025). Multi-objective data migration in container-based heterogeneous cloud environments using deep adaptive dragonfly optimization. *International Journal of Information Technology*. <https://doi.org/10.1007/s41870-025-02557-2>
- [10] Nanni, L., Brahnam, S., Loreggia, A., et al (2023). Heterogeneous Ensemble for Medical

- Data Classification. Analytics. <https://doi.org/10.3390/analytics2030037>
- [11] He, Q., Wu, M., Zhang, P., et al (2025). Multimodal Image Segmentation with Dynamic Adaptive Window and Cross-Scale Fusion for Heterogeneous Data Environments. Applied Sciences. <https://doi.org/10.3390/app151910813>
- [12] Wu, M., Xu, Z., Zheng, L. (2025). Heterogeneous graph contrastive learning with adaptive data augmentation for semi-supervised short text classification. Expert Systems. <https://doi.org/10.1111/exsy.13744>
- [13] Yilmaz, S., Zarro, C., Hayvaci, H., et al (2021). Adaptive Waveform Design with Multipath Exploitation Radar in Heterogeneous Environments. Remote Sensing. <https://doi.org/10.3390/rs13091628>
- [14] Museba, T., Nelwamondo, F., Ouahada, K. (2021). An Adaptive Heterogeneous Online Learning Ensemble Classifier for Nonstationary Environments. Computational Intelligence and Neuroscience. <https://doi.org/10.1155/2021/6669706>
- [15] Verma, A., Saha, R., Kumar, G., et al (2024). VAIDANSHH: Adaptive DDoS detection for heterogeneous hosts in vehicular environments. Vehicular Communications. <https://doi.org/10.1016/j.vehcom.2024.100787>
- [16] Han, M., Yang, S., Wu, H., et al (2024). Multi-Label Classification Algorithm for Adaptive Heterogeneous Classifier Group. Mathematics. <https://doi.org/10.3390/math13010103>
- [17] Li, Y., Jian, C., Zang, G., et al (2024). Node classification oriented Adaptive Multichannel Heterogeneous Graph Neural Network. Knowledge-Based Systems. <https://doi.org/10.1016/j.knosys.2024.111618>
- [18] Yang, S., Tang, S., Cai, Y., et al (2025). Self-Adaptive Reflectance Film for Passive Temperature Regulation in Diverse Environments. Advanced Science. <https://doi.org/10.1002/advs.202415121>
- [19] Pourkamali-Anaraki, F., Bennete, W. (2021). Adaptive Data Compression for Classification Problems. IEEE Access. <https://doi.org/10.1109/access.2021.3130551>
- [20] Ximing, C., Xilong, H., Du, C., et al (2025). FedMEM: Adaptive Personalized Federated Learning Framework for Heterogeneous Mobile Edge Environments. International Journal of Computational Intelligence Systems. <https://doi.org/10.1007/s44196-025-00814-7>
- [21] Shi, C., Jiang, B., Xu, H., et al (2026). Adaptive Collaborative DNN Inference via Heterogeneous Graph Attention in Edge Environments. IEEE Internet of Things Journal. <https://doi.org/10.1109/jiot.2025.3648047>
- [22] Zhou, H., Rahman, S., Angelova, M., et al (2025). A robust and generalized framework in diabetes classification across heterogeneous environments. Computers in Biology and Medicine. <https://doi.org/10.1016/j.compbimed.2025.109720>
- [23] Mofrad, S., Ahmed, I., Zhang, F., et al (2022). Securing Big Data Scientific Workflows via Trusted Heterogeneous Environments. IEEE Transactions on Dependable and Secure Computing. <https://doi.org/10.1109/tdsc.2021.3123640>
- [24] Tishkovskaya, S., Blackwell, P. (2021). Bayesian estimation of heterogeneous environments from animal movement data. Environmetrics. <https://doi.org/10.1002/env.2679>
- [25] Wang, J., Zhuang, Y., Yan, F., et al (2025). Density Adaptive Registration of Large-Scale Point Clouds in Diverse Outdoor Environments. IEEE Robotics and Automation Letters. <https://doi.org/10.1109/lra.2025.3549659>
- [26] Besbes, O., Ma, W., Mouchtaki, O. (2022). Beyond IID: Data-Driven Decision-Making in Heterogeneous Environments. SSRN Electronic Journal. <https://doi.org/10.2139/ssrn.4140928>
- [27] Saxena, D., Singh, A., Lindenstruth, V. (2026). QuAd-caching management model for heterogeneous data lake environments. Expert Systems with Applications. <https://doi.org/10.1016/j.eswa.2025.129133>
- [28] Zhang, M., Wang, W. (2021). Weighted Adaptive Partition for Heterogeneous IoT Data Stream. IEEE Internet of Things Journal. <https://doi.org/10.1109/jiot.2020.3045726>
- [29] Halgamuge, M., Niyato, D. (2025). Adaptive edge security framework for dynamic IoT security policies in diverse environments. Computers & Security. <https://doi.org/10.1016/j.cose.2024.104128>
- [30] Bae, H. (2024). Evaluation of Malware Classification Models for Heterogeneous Data. Sensors. <https://doi.org/10.3390/s24010288>