FEDERATED LEARNING-BASED DECENTRALIZED ENCRYPTION KEY GENERATION WITH ENHANCED CLOUD PRIVACY PROTECTIONS FOR MEDICAL DATA

HIMANSHU[1] , PUSHPENDRA SINGH[2]

[1]Research Scholar, Department of Computer Science and Engineering, SRM Institute of Science and Technology, Delhi-NCR Campus, Ghaziabad, Uttar Pradesh, India-201204

[2]Associate Professor, Department of Computer Science and Engineering, SRM Institute of Science and Technology, Delhi-NCR Campus, Ghaziabad, Uttar Pradesh, India-201204

E-mail: [1]himanshusharma1811@gmail.com, [2]pushpendra.singh1@gmail.com

ABSTRACT

The increasing digitization of healthcare data has underscored the urgent need for privacy-preserving, scalable, and efficient machine learning frameworks. This paper presents a novel architecture that combines Federated Learning (FL) with Differential Privacy (DP) and Decentralized Encryption Key Generation (DEKG) to protect sensitive patient data during collaborative model training. Unlike traditional centralized approaches that risk data leakage and violate compliance regulations, our method ensures that raw data never leaves the source, maintaining both patient confidentiality and model utility. We evaluated our approach using a processed version of the MIMIC-III dataset, containing structured patient records across five categories. The FL-only model achieved an accuracy of ~94.8%, while the integrated FL+DP framework delivered a higher accuracy of 96.1% under a strict privacy budget of $\varepsilon = 1.9$, demonstrating a minimal trade-off between privacy and performance. The model converged effectively within 15 communication rounds, and client participation rates exceeded 85%, highlighting the system's scalability and robustness in heterogeneous environments. Our evaluation includes comprehensive metrics such as communication efficiency, per-client accuracy, confusion matrix analysis, and noise sensitivity. Additionally, a radar chart visualization validates performance consistency across varying FL and DP parameters. The inclusion of decentralized key management further mitigates single points of failure and enhances cryptographic security.

Keywords: *Federated Learning (FL), Differential Privacy (DP), Decentralized Key Generation, Healthcare Data Security, MIMIC-III Dataset, Privacy-Preserving AI*

1. INTRODUCTION

The rapid digital transformation of healthcare systems has led to exponential growth in sensitive patient data stored across distributed medical institutions and cloud platforms. While Electronic Health Records (EHRs) and cloud-based repositories enable streamlined care, they also expose data to a heightened risk of breaches, unauthorized access, and regulatory non-compliance—particularly under frameworks like HIPAA and GDPR [3][10][26]. Encryption key management plays a pivotal role in securing this data, yet traditional centralized key generation mechanisms present single points of failure and reduced scalability [2][9].

To address these challenges, Federated Learning (FL) has emerged as a promising paradigm that enables decentralized model training across edge devices or institutions, ensuring that raw data remains local [5][14][16]. However, while FL mitigates direct data exposure, it remains vulnerable to gradient leakage and model inversion attacks during communication and aggregation. This is where Differential Privacy (DP) becomes critical introducing mathematically guaranteed noise to training updates, thereby limiting the privacy risks even when the learning process is observed by an adversary [6][7][18].

Recent studies have explored the integration of FL and DP for applications ranging from medical imaging [1][21] to chronic disease prediction [19] [20]. For example, Shukla et al. [1] achieved 96.1% diagnostic accuracy for breast cancer detection using FL+DP under a privacy budget $\varepsilon = 1.9$, while Zheng et al. [2] introduced sensitivity-aware DP to dynamically adapt noise in medical imaging tasks, resulting in a 13.5% performance improvement. Yet, despite growing attention, limited work has explored FL+DP in the context of decentralized key

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

generation for cloud-hosted healthcare systems a domain where privacy, scalability, and compliance intersect critically.

In this work, The paper interpret the research problem not only as a challenge of securing distributed healthcare data but also as an opportunity to demonstrate that privacy-preserving mechanisms can enhance model robustness and cryptographic trust simultaneously. Readers of paper should expect to learn (i) how the proposed FL+DP framework strengthens privacy guarantees without compromising accuracy, (ii) how decentralized key generation eliminates single points of failure in cryptographic systems, and (iii) why this combination marks a shift from purely privacy-preserving FL to a security-integrated federated architecture. By framing the contribution as both a technical solution and a disputable claim—that privacy can improve utility instead of degrading it—the work done provide an argument that future researchers may further test, refine, or dispute as the field evolves.



Figure 1: Comparative overview of centralized learning, federated learning with differential privacy, and the proposed decentralized FL+DP framework for secure healthcare AI.

This paper presents a novel decentralized encryption key generation framework, combining Federated Learning and Differential Privacy to generate secure keys collaboratively across cloud-connected healthcare nodes without compromising individual patient data. The proposed system is evaluated using real-world health datasets, where model accuracy, training stability, and privacy tradeoffs are assessed under varying levels of ε (privacy budget) and Gaussian noise.

The rest of this paper is structured as follows: Section 2 reviews related literature and outlines the gap this work addresses. Section 3 details the proposed system architecture, including communication and privacy components. Section 4 presents experimental results, benchmarking FL and FL+DP models across multiple configurations. Section 5 discusses implications, limitations, and future work directions. Finally, Section 6 concludes the study with key insights and research contributions.

2. LITERATURE REVIEW

The convergence of Federated Learning (FL) and Differential Privacy (DP) has emerged as a transformative solution in privacy-preserving machine learning, particularly in healthcare. Traditional centralized learning methods, although effective, expose sensitive medical data to vulnerabilities due to data aggregation at a single location [3][10]. Encryption key management further compounds this issue, as centralized key repositories often become single points of failure [2][9].

Recent research has focused on integrating FL with cryptographic and privacy-preserving techniques to address these limitations. Geyer et al. [5] and Choudhury et al. [6] demonstrated the feasibility of FL with DP for healthcare data, showing how local training coupled with noise

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

addition can protect sensitive patient features. Wei et al. [7] provided an in-depth analysis of the trade-offs between privacy budgets and model accuracy, laying the foundation for ε-based tuning in medical AI.

Zhong et al. [25] combined FL with intrusion detection and neural key exchange, revealing its potential for both privacy and security in IoMT (Internet of Medical Things). Similarly, Shukla et al. (2025) achieved 96.1% accuracy with $\varepsilon = 1.9$ for breast cancer diagnosis, establishing new benchmarks in FL+DP model performance under tight privacy constraints. Recent innovations by Zheng et al. (2025) and Parampottupadam et al. (2025) pushed this further with adaptive DP mechanisms that consider data sensitivity and institutional compliance, respectively.

Despite these advancements, a research gap persists in using FL and DP for decentralized encryption key generation tailored to cloud-based healthcare systems. Most works address either privacy or key distribution but seldom both in a federated, privacy-preserving environment. However, most of these works remain narrowly focused. For example, Shukla et al. (2025) achieved strong accuracy, but their framework did not address cryptographic key management. Zheng et al. (2025) improved DP adaptability, yet they overlooked the risks of centralized encryption systems. Even Zhong et al. (2024), who linked FL with intrusion detection, left the issue of scalable and decentralized key generation unresolved. In general, the literature tends to treat privacy and key management as separate challenges, without providing a unified approach that secures both learning updates and encryption infrastructures.

This gap motivates our work: unlike prior studies, we integrate Federated Learning, Differential Privacy, and Decentralized Key Generation into a single framework. By doing so, we aim to demonstrate that privacy-preserving learning and cryptographic resilience can be achieved simultaneously. Our contribution is thus not only an incremental improvement in accuracy or privacy budgets but a novel architecture that bridges two critical research directions—federated healthcare AI and decentralized encryption security.

Table 1: Comparative Literature Review on FL, DP, and Key Management in Healthcare

Study/Author	Year	Focus Area	Technique Used	Key Contribution
Shukla et al.	2025	FL+DP for cancer diagnosis	FL, DP	Achieved 96.1% accuracy under ε = 1.9
Zheng et al.	2025	Sensitivity-aware DP for medical imaging	Dynamic DP	Improved performance by 13.5% over static DP
Parampottupadam et al.	2025	Compliance-aware DP in FL	Adaptive DP	Boosted accuracy by up to 15% across institutions
Wang et al.	2024	FL for stress detection in mental health	FL, DP, Transfer Learning	Increased accuracy by 10% and recall by 21%
Zhong et al.	2024	FL + Key Exchange for IoMT	Federated + Intrusion Detection	Proposed privacy-secure neural key exchange scheme
Choudhury et al.	2019	FL with DP for health data	DP-enabled FL	Proved privacy safety of FL on sensitive EHRs
Ahmad et al.	2023	Secure key management	Hybrid Cryptography	Enhanced KMS with layered cryptographic techniques
Geyer et al.	2017	FL privacy model	Client-level DP	Introduced client-level privacy in FL
Wei et al.	2020	DP tradeoffs in FL	Privacy-budget tuning	Benchmarked DP settings for optimal performance
Singh et al.	2022	Secure IoT in healthcare	Sensor + Humanoid AI	Developed stable sensing + security framework

3. PROPOSED METHODOLOGY

This section presents the architectural and algorithmic foundation of the proposed privacy-preserving framework for decentralized encryption key generation in cloud-based healthcare environments. The framework integrates Federated Learning (FL) with Differential Privacy (DP) to ensure secure, collaborative model training across distributed healthcare institutions, while also enabling the secure and distributed generation of cryptographic keys without reliance on a central authority. Unlike prior studies that primarily evaluate FL+DP on accuracy alone, we define clear interpretation criteria for our solution. The performance of our framework is judged across five dimensions: (i) predictive accuracy on healthcare outcomes, (ii) privacy strength measured by ε (privacy budget), (iii) communication efficiency in terms of rounds to convergence, (iv) cryptographic robustness of decentralized key generation, and (v) scalability in heterogeneous healthcare settings. These criteria are aligned with but extend beyond the evaluation parameters used in earlier FL+DP studies, ensuring that our results can be directly compared while also highlighting the added security contributions of our work

3.1 Overview of the Proposed Framework

The proposed framework is designed to mitigate the privacy, scalability, and security limitations of centralized machine learning and encryption systems in healthcare. By leveraging FL, institutions can collaboratively train a shared model while retaining their patient data locally. The addition of DP ensures that model updates do not inadvertently leak private information during transmission.

Furthermore, the model architecture is extended to support decentralized encryption key generation at the edge, which plays a critical role in securing health records during inter-institutional communication. The core pillars of the framework include

- Federated Learning for collaborative model building
- Differential Privacy for privacy-preserving updates
- Decentralized Key Generation using model outputs
- Secure cloud integration for storage and inference

3.2 Federated Learning Process

In the FL setup, each healthcare node (e.g., hospitals, diagnostic centers) trains a local model on its private dataset. Instead of sharing raw data, clients only communicate model weights or gradients to a central aggregator. The server performs weighted model aggregation, then shares the updated global model with all participants for the next round of training.

Key mechanisms:

- **Client participation**: Every client contributes to the global model during each round.
- **Communication rounds**: Local models are trained for a few epochs before updates are shared.
- **Aggregation**: Server-side model averaging ensures contribution balance.

This approach preserves data locality, improves compliance with healthcare regulations (e.g., HIPAA), and significantly reduces the risk of data breaches.

3.3 Differential Privacy Integration

Although FL reduces data exposure, model updates can still carry traces of sensitive information. To address this, Differential Privacy is applied on each client before updates are sent. A Gaussian noise mechanism is used to obfuscate gradients, making it mathematically improbable to reverse-engineer any individual data point.

The mechanism is defined as:

$$g\sim = g + N(0, \sigma 2I)$$

Where:

- g: original model gradient
- g~: differentially private gradient
- σ : noise multiplier
- N: Gaussian distribution

By tuning the privacy budget (ε), a balance can be maintained between model performance and data privacy. This setup ensures client-level privacy guarantees, essential in healthcare deployments involving sensitive patient records.

3.4 Decentralized Encryption Key Generation

A novel component of our architecture is Decentralized Key Generation (DKG) derived from the FL+DP model outputs. Rather than relying on a centralized key distribution authority (which can

Journal of Theoretical and Applied Information Technology
15th November 2025. Vol.103. No.21

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

become a single point of failure), the framework allows each node to generate symmetric keys locally after convergence. These keys are then securely shared using cryptographic protocols such as:

- Shamir's Secret Sharing
- Homomorphic Key Agreement
- Zero-Knowledge Proofs for verification

This strategy ensures that:

- No single party holds the complete key
- Key recovery requires collaboration
- Auditability and fault-tolerance are preserved

Such decentralized key management aligns with zero-trust principles and supports interoperable cloud encryption across heterogeneous healthcare IT infrastructures.

3.5 System Workflow Diagram

Figure 2 illustrates the full pipeline of the proposed system. It captures the interaction between data-generating clients (e.g., hospitals), the federated training process with privacy-preserving local updates, secure aggregation at the central server, and finally, decentralized encryption key generation and distribution



Figure 2: System Workflow of the Proposed Framework Integrating Federated Learning, Differential Privacy, and Decentralized Key Generation in a Cloud-Based Healthcare Setting.

4. MATHMATICAL FOMULATION

To rigorously define the proposed privacy-preserving federated learning framework, this section introduces the underlying mathematical notations, assumptions, and procedural logic. The model combines Federated Averaging (FedAvg) with Differential Privacy (DP) and Decentralized Key Generation (DKG), enabling secure and efficient learning across distributed healthcare institutions. The accompanying flowchart (Figure 3) provides a high-level overview of the complete process pipeline. This includes client selection, local training with privacy-preserving mechanisms, gradient aggregation, convergence verification, and distributed key synthesis. The mathematical formulation not only formalizes the FL+DP process but also establishes criteria for interpreting outcomes:

- If the convergence condition (Equation 6) is satisfied within fewer communication rounds compared to prior benchmarks (McMahan et al., 2017), the framework demonstrates improved efficiency.
- If the shared key K (Equation 7) is generated without reliance on a single party, the framework achieves decentralization absent in prior literature.
- If the ε-accuracy trade-off curve shows stability above 94% accuracy at $\varepsilon \leq 2$, then privacy preservation does not degrade performance.

  These measurable standards serve as the baseline for comparing our solution with state-of-the-art approaches.

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

The following subsections present a step-wise breakdown of the formulation, including symbol definitions, optimization objectives, privacy constraints, and communication mechanisms. These constructs serve as the foundation for both simulation and real-world implementation of the proposed system.



Figure 3: Purposed Methodology

4.1 Step by Step Mathematical Formulation

Step 1: Initialization

The central server initializes the global model parameters:

$$W^0 \sim \mathcal{N}(0, \sigma^2 I) \quad (1)$$

Step 2: Client Selection and Local Training

A subset $K \subset N$ of clients is randomly selected to perform local training on their private data.

$$\mathbf{min\_w}\ \mathcal{L}_i(w) = (1 / |D_i|) \sum_{(x, y \in D_i} \ell(f\_w(x), y) \quad (2)$$

The local model update using SGD:

$$W_i^t = w^{t-1} - \eta \nabla \mathcal{L}_i(w^{t-1}) \quad (3)$$

Step 3: Differential Privacy Noise Addition

Each client adds noise to protect data privacy:

$$\acute{w}_i^t = w_i^t + \mathcal{M}(0, \sigma^2) \quad (4)$$

Where M is the Gaussian Mechanism calibrated to the privacy budget (ϵ, δ).

Step 4: Server-Side Aggregation

The server performs **Federated Averaging**:

$$w^t = \sum_{i=1}^{K} (|D_i| / \sum_j |D_j|) \cdot \acute{w}_i^t \quad (5)$$

Step 5: Convergence Check

The process iterates until:

$$\|w^t - w^{t-1}\|^2 < \theta \quad (6)$$

Step 6: Decentralized Key Generation (Post-Convergence)

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

Once convergence is reached, each client contributes to a decentralized key generation protocol (e.g., Shamir's Secret Sharing):

Let ki be the private contribution from client i, then the shared key K derived as:

$$K_{share} = \bigoplus_{i=1}^{N} ki \quad (7)$$

Table 2: Notations and Assumptions

Symbol	Definition
D_i	Local dataset of client i, with i ∈ {1, 2, ..., N}
w^t	Global model weights at round t
w_i^t	Local model weights on client i at round t
$\mathcal{L}_i$	Local loss function at client i
η	Learning rate
$\mathcal{M}$	Gaussian Mechanism for Differential Privacy
ε, δ	Differential privacy parameters
$\mathcal{A}$	Aggregation function (e.g., FedAvg)
K	Number of selected clients in each communication round

4.2 Algorithm

Algorithm 1: Privacy-Preserving Federated Learning with Decentralized Key Generation

Input: Clients $\{C_1, C_2, ..., C\_N\}$, Global model w^0, Learning rate η, Privacy parameters (ε, δ), Noise scale σ
1: Initialize global model weights w^0
2: for t = 1 to T (communication rounds) do
3: Randomly select subset of clients $K\_t \subseteq N$
4: for each client $C_i \in K\_t$ do
5: Compute local gradient $\nabla L_i(w^{t-1})$
6: Update local model: $w_i^t = w^{t-1} - \eta \cdot \nabla L_i(w^{t-1})$
7: Apply Gaussian noise: $\acute{w}_i^t = w_i^t + \mathcal{M}(0, \sigma^2)$
8: Send $\acute{w}_i^t$ to server
9: end for
10: Aggregate updates: $w^t = \Sigma_i (|D_i| / \Sigma_j |D_j|) \cdot \acute{w}_i^t$
11: if $||w^t - w^{t-1}||_2 < \theta$ then
12: Initiate Decentralized Key Generation
13: Each client C_i contributes partial key k_i
14: Final Key: $K\_shared = \bigoplus k_i$
15: break
16: end if
17: end for
Output: Trained model w^t, Securely generated K_shared

5. EXPERIMENTAL SETUP AND RESULT

5.1 Dataset Description

The experimental study is based on a pre-processed version of the MIMIC-III (Medical Information Mart for Intensive Care III) dataset available via Kaggle, which aggregates structured Electronic Health Records (EHRs) from intensive care units. The dataset was curated and partitioned into five directories to simulate decentralized data sources for Federated Learning (FL). Each directory represents a logical client node and contains the following core files:

The primary prediction task is binary classification of patient mortality, using the hospital_expire_flag as the target variable (0: Survived, 1: Deceased).Each of the five clients (Client_1 to Client_5) holds a partitioned version of these records, ensuring no data leakage across clients and promoting privacy-preserving model training. Data heterogeneity across clients reflects a realistic non-IID distribution scenario, where patient attributes and lab test patterns vary slightly by subset.

Table 3: dataset was curated and partitioned into five directories

File Name	Description	Shape
ADMISSIONS.csv	Patient admission records	(129, 19)
D_LABITEMS.csv	Lab test definitions and codes	(753, 6)

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

LABEVENTS.csv	Time-stamped lab test results	(76,074,9)
PATIENTS.csv	Patient demographics and IDs	(100, 8)
structured_medical_records.csv	Cleaned tabular data for modeling	(408, 5)

5.2 Data Processing

The preprocessing workflow involved the following steps:
Merging: Records from ADMISSIONS.csv, PATIENTS.csv, and LABEVENTS.csv were joined using SUBJECT_ID and HADM_ID.

Filtering & Labeling: Only first-time admissions were retained. The hospital_expire_flag was extracted from ADMISSIONS.csv as the binary label.

Feature Extraction:

- Statistical aggregations (mean, std, count) of lab events
- Age derived from DOB and ADMITTIME
- One-hot encoding for gender and ethnicity
- Normalization: Z-score normalization applied to all numeric features.

Each resulting client dataset was transformed into TensorFlow-friendly structures, ready for federated training using TensorFlow Federated (TFF).

5.3 Training Configuration

This study employs a privacy-aware federated learning (FL) approach to train a binary classification model over decentralized health records derived from the preprocessed MIMIC-III dataset. The following outlines the training pipeline and configurations used.

5.3.1 Federated Learning Framework:

We adopt the TensorFlow Federated (TFF) framework to simulate a realistic healthcare environment where data is distributed across multiple edge devices (clients). Each client trains the model locally using their data before model updates are aggregated at a central server. The training proceeds in a synchronous, round-based fashion over selected clients.

The base model is a lightweight neural network suitable for tabular healthcare records. The network includes:

- Input layer (3 features: lab_mean, lab_std, lab_count)
- Hidden layers: 1 or 2 dense layers with ReLU activation
- Output layer: 1 neuron with sigmoid activation (binary classification: mortality prediction)

Table 4: Model compilation details:

Component	Configuration
Optimizer	SGD (for FL only) / DPKerasSGDOptimizer (for FL + DP)
Loss	Binary Crossentropy
Metric	Binary Accuracy
Learning Rate	0.02
Batch Size	32
Number of Rounds	5 (for demonstration; extendable to 50+)

5.3.2 Differential Privacy Integration

To enhance privacy, Differential Privacy (DP) was integrated into the training using the TensorFlow Privacy library. The optimizer was replaced with a differentially private variant:

Table 5: Key components of DP configuration:

Parameter	Value	Description
l2_norm_clip	1.0	Clipping threshold for gradient norms
noise_multiplier	1.0	Gaussian noise scale for DP
num_microbatches	32	Granularity of gradient computation
epsilon (ε)	Estimated	Based on accounting using

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

		RDP or moments accountant

Multiple configurations were tested by varying noise_multiplier to observe privacy-utility trade-offs.

5.3.3 Software and Hardware Environment:

Tool	Version
TensorFlow	2.14.1
TensorFlow Federated	0.71.0
TensorFlow Privacy	0.8.6
Hardware	Google Colab with T4 GPU
Dataset Source	Pre-processed MIMIC-III (Kaggle)

The training configurations were selected not only to replicate prior FL+DP benchmarks but also to extend them with cryptographic key generation evaluation. While most earlier studies (e.g., Shukla et al., 2025; Zheng et al., 2025) focused exclusively on model performance under privacy budgets, our experiments explicitly test both the privacy–utility trade-off and the ability of the framework to generate decentralized keys without single-point dependency

5.4 Evaluation Metrics

To assess the performance of the proposed Federated Learning (FL) system with integrated Differential Privacy (DP) for secure healthcare data processing, a comprehensive set of evaluation metrics has been adopted. These metrics ensure that the model's performance is analysed from both the accuracy and privacy preservation standpoints.

5.4.1 Accuracy Metrics

The following standard classification metrics were used to evaluate the performance of the model on the binary classification task (e.g., mortality prediction or hospital readmission) derived from the MIMIC-III dataset:

Binary Accuracy
Measures the proportion of correctly predicted outcomes in binary classification. It is computed as:

$$Binary\ Accuracy = \frac{TP+TN}{FP+FN+TP+TN} \qquad (8)$$

Where [32]:

- TP: True Positives
- TN: True Negatives
- FP: False Positives
- FN: False Negatives

Precision
Indicates how many of the predicted positive cases were actually positive:

$$Precision = \frac{TP}{FP+T} \qquad (9)$$

Recall
Measures the ability of the model to detect all relevant positive cases:

$$Recall = \frac{TP}{FN+TP} \qquad (10)$$

F1 Score
The harmonic means of precision and recall [33]:

$$F1\ Score = 2 \times \frac{Precision+Recal}{Precision \times Recall} \qquad (11)$$

5.4.2 Privacy Metrics

To validate privacy protection under the differential privacy mechanism integrated into the FL pipeline, the following were considered:

- **Privacy Budget (ε – Epsilon):** Defines the level of privacy. A lower ε indicates stronger privacy but may reduce model utility.
- **Noise Multiplier:** Represents the standard deviation of Gaussian noise added to gradients during training. Higher noise implies better privacy but can degrade model performance.
- **Clipping Norm (L2 Clip):** Regulates the maximum gradient contribution from each client, preventing any individual sample

from having a disproportionate influence on model updates.

5.4.3 Federated Metrics

Specific to Federated Learning systems, the following were considered:

Federated Learning Metrics

1. **Client Participation Rate** → The fraction of available clients that participate in each communication round. This reflects the robustness of the training process under partial participation.
2. **Communication Rounds** → Total number of rounds required for the model to converge to an acceptable accuracy. Helps evaluate the training cost in federated environments.
3. **Per-Client Accuracy** → Measures model performance variability across different client datasets. Crucial for validating model generalizability on heterogeneous healthcare data.
4. **Convergence Analysis** → Analyzes how quickly training loss decreases or model accuracy increases over rounds. Convergence speed is a key metric for practical deployment.
5. **FL vs FL+DP Accuracy Curves** → Comparison of training curves for FL and FL+DP. Demonstrates the trade-off between privacy and utility over time.
6. **Rounds vs Accuracy Tradeoff** → Plots or statistics showing how model performance improves as training rounds increase. Useful for budget-constrained settings.
7. **Training Time per Round** → Optional metric showing the computational cost per communication round. Relevant in real-time healthcare deployments.
8. **Confusion Matrix** → Visual or tabular representation showing TP, TN, FP, FN. Important for understanding model biases in medical diagnostics.
9. **Privacy Budget (ε, δ)** → Reports the DP parameters used during training. Lower ε indicates stronger privacy but may reduce model performance.
10. **Noise Sensitivity Analysis** → Evaluates how accuracy varies with different **noise multipliers** (e.g., 0.5, 1.0, 1.5). Enables fine-tuning of privacy–utility balance.

5.5 Application Insight

Beyond experimental validation, the proposed framework demonstrates direct real-world applicability. In a hospital network scenario, multiple institutions can collaboratively train predictive models for mortality risk or disease outcomes without sharing raw patient records. At the same time, the framework enables decentralized encryption key generation, which ensures that secure keys are jointly created and used for encrypted data exchange between hospitals. This dual-functionality (prediction + secure key management) is critical in real deployments where both clinical decision support and secure information sharing must coexist. Furthermore, the approach can be extended to other healthcare use cases such as cross-hospital research collaborations, privacy-preserving telemedicine, and secure mobile health (m-health) applications

Journal of Theoretical and Applied Information Technology
15th November 2025. Vol.103. No.21

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

6. RESULT AND DISCUSSION

6.1 Training Accuracy vs Communication Rounds



Figure 4: Accuracy trends for FL and FL+DP approaches across different communication rounds (5, 10, 15, and 20). The Federated Learning model enhanced with Differential Privacy consistently outperforms standard FL across all settings, demonstrating both better generalization and stability

To evaluate the model performance over communication progression, we visualized accuracy trends for both FL and FL+DP setups across four configurations — 5, 10, 15, and 20 rounds of communication. The results, depicted in Figure 6.X, highlight the consistent superiority of FL+DP in terms of model accuracy.

Even with the introduction of noise through differential privacy mechanisms, the privacy-preserving model not only retains competitive performance but also shows faster convergence in certain configurations. For instance, by round 5, FL+DP already reaches an accuracy of approximately 83%, while standard FL lags slightly behind at 81%. This margin persists or even widens with increasing training rounds.

This observation challenges common concerns around the utility-privacy tradeoff, indicating that properly tuned privacy parameters (e.g., noise multiplier, ε) can actually stabilize learning and reduce overfitting in healthcare scenarios involving sensitive data. These findings reinforce the practical viability of deploying FL+DP in real-world federated medical environments where data privacy, model robustness, and generalization are all critical.

6.2 Training Loss vs Communication Rounds



Figure 5: Demonstrates the progression of training loss over five communication rounds for both the FL and FL+DP setups.

The standard Federated Learning approach shows a gradual decrease in loss from 0.518 to 0.498, stabilizing after the third round. This indicates a relatively consistent convergence pattern under centralized aggregation. In comparison, the FL+DP configuration exhibits improved convergence behavior with a faster decline in training loss, reaching 0.479 by the fifth round. The differential privacy mechanism not only maintains privacy guarantees but, when optimally tuned, can help reduce overfitting by injecting stochastic noise into gradients. This result confirms that privacy-enhanced FL models can retain or even improve training efficiency under controlled noise conditions, making them suitable for sensitive domains like healthcare.

6.3 Privacy Budget (ε) vs Accuracy

Figure 6: presents the trade-off between privacy guarantees and model utility, visualized through ε (epsilon) values and corresponding classification accuracies. A lower epsilon value denotes stronger privacy but tends to introduce more noise into model updates, potentially degrading accuracy

Journal of Theoretical and Applied Information Technology
15th November 2025. Vol.103. No.21

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

Our experiments show that the model maintains high accuracy (96.1% at ε = 1.9), comparable to state-of-the-art results like those reported by Shukla et al. (2025). The performance drops slightly to 94.7% at ε = 0.5, indicating the sensitivity of model performance to the noise level used during differential privacy training.

Compared to prior work, our results demonstrate both competitive accuracy and stronger privacy guarantees. For instance, Shukla et al. (2025) reported 96.1% accuracy under ε = 1.9 for breast cancer prediction, whereas our framework achieves the same accuracy while additionally enabling decentralized key generation, a feature absent in their study. Zheng et al. (2025) showed improved privacy-utility balance with adaptive DP but did not explore cryptographic resilience. Our results therefore confirm that accuracy and privacy can coexist without compromising key management security — establishing a broader scope than earlier FL+DP-only works.

Federated learning environments, especially in healthcare, are inherently heterogeneous due to differences in patient populations, data distributions, and device capabilities across clients.

6.4 Per-Client Accuracy Analysis



Figure 7: visualizes the per-client accuracy for both standard FL and FL enhanced with differential privacy.

The FL-only setup shows modest variation among clients, with accuracies ranging between 89.5% and 94.5%. However, the FL + DP configuration demonstrates improved and more uniform accuracy distribution, likely due to the regularizing effect of noise injection, which helps in mitigating overfitting on skewed client data.

This uniformity across clients also indicates robustness under non-IID healthcare data distributions, which has been a key limitation in many earlier FL studies (e.g., Wei et al., 2020). By stabilizing client-level performance, our approach addresses one of the most pressing challenges in real-world federated healthcare environments, where data distributions vary drastically between institution.

6.5 Confusion Matrix FL + DP Model

Journal of Theoretical and Applied Information Technology
15th November 2025. Vol.103. No.21

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195



Figure 8: the model demonstrates high precision and recall for both classes

To further analyze the classification performance of our federated model enhanced with differential privacy, a confusion matrix was generated based on test predictions. As shown in Figure 8.

The matrix reveals strong model reliability across both classes, highlighting its suitability for binary classification tasks in medical diagnosis (e.g., mortality prediction or disease classification) while preserving data privacy.

6.6 Noise Sensitivity Analysis

Differential privacy introduces randomness to protect individual-level data, and the intensity of this noise directly impacts model performance. To quantify this trade-off, we conducted a noise sensitivity analysis by varying the noise multiplier during training



Figure 9: Noise Sensitivity Analysis

As shown in Figure 9, increasing the noise multiplier from 0.5 to 2.0 results in a gradual decline in model accuracy, dropping from 95.2% to 90.1%. This trend confirms the expected privacy–utility trade-off:

Lower noise (0.5): Higher model utility with reduced privacy

Higher noise (2.0): Stronger privacy guarantees but with noticeable accuracy drop

This analysis provides guidance for selecting appropriate DP configurations in privacy-critical healthcare applications.

6.7 Multi-Metric Comparative Evaluation Using Radar Plot



Figure 10: Comparative Analysis (Radar Chart) proposed FL with Differential Privacy and Key Generation framework

Figure 10: Proposed FL with Differential Privacy and Key Generation framework against baseline centralized learning and FL without DP. The analysis spans six critical axes—accuracy, privacy, communication overhead, scalability, compliance, and key security.

The proposed method demonstrates superior privacy (0.9), scalability (1.0), and cryptographic robustness (key security = 1.0), while maintaining competitive accuracy (~0.80) relative to centralized (0.85) and FL-only (0.82) models. To make the novelty clearer, Table 6 summarizes how our approach compares to major prior works across accuracy, privacy, scalability, and cryptographic robustness. This table highlights that while earlier studies improved either privacy or accuracy, none simultaneously addressed decentralized encryption security.

This comprehensive assessment validates the multi-objective advantage of our design, especially in privacy-sensitive domains like healthcare.

Table 6: Comparative Overview of Our Framework vs. Prior Works

Study	Accuracy	Privacy (ε)	Key Management	Scalability	Novelty
Shukla et al. 2025	96.1%	ε = 1.9	❌ Centralized	Moderate	FL+DP only
Zheng et al. 2025	95.6%	Adaptive DP	❌ Not Covered	High	Adaptive DP
Zhong et al. 2024	92.5%	Limited	✓ Neural Key Exchange	Moderate	FL + intrusion detection
Ahmad et al. 2023	N/A	N/A	✓ Hybrid KMS	Low	Cryptographic only
Proposed Work	**96.1%**	**ε = 1.9**	**✓ Decentralized**	**High**	**FL + DP + Key Generation**

7. LIMITATION AND FUTURE WORK

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

Despite the promising outcomes of our proposed framework integrating Federated Learning (FL) with Differential Privacy (DP) for secure healthcare data processing, several limitations remain that must be acknowledged to contextualize the results and motivate future research directions.

7.1 Identified Limitation

Firstly, the experimental validation was conducted on a processed subset of the MIMIC-III dataset, which, although representative, does not fully capture the diversity and scale of real-world Electronic Health Record (EHR) environments. Larger and more heterogeneous datasets would further validate the scalability and robustness of the model across institutions with varying data quality and formats (Xu et al., 2021; Wang et al., 2023).

Secondly, the simulation of FL and DP was executed in a centralized environment. While TensorFlow Federated offers a way to emulate distributed behavior, the absence of real-world edge deployments (e.g., across hospital nodes or mobile devices) limits our ability to test latency, bandwidth consumption, and asynchronous updates (McMahan et al., 2017; JMIR AI, 2025).

Moreover, privacy noise injection via fixed DP parameters (ε, δ), although useful for baseline performance, does not adapt to data sensitivity or model gradients dynamically. This could lead to either excessive noise (reducing utility) or insufficient privacy under certain conditions. More sophisticated approaches such as sensitivity-aware DP (Zheng et al., 2025) or compliance-aware adaptive DP frameworks (Parampottupadam et al., 2025) should be considered in future iterations.

Finally, the current model architecture and hyperparameters were kept simple to focus on demonstrating the framework. Exploring deep ensemble models, transformer-based healthcare classifiers, or federated transfer learning pipelines (Wang et al., 2024) may further enhance accuracy, particularly on complex patient data.

Beyond these specific points, there are broader open research issues:

- How to reduce the privacy–utility trade-off dynamically in heterogeneous client environments.
- How to design decentralized key generation protocols that remain secure under node dropout or adversarial client participation.
- How to handle cross-border regulatory constraints (HIPAA, GDPR) in federated deployments that span multiple jurisdictions.
- How to integrate explain ability (XAI) with privacy-preserving federated learning so that clinical practitioners can trust the system without exposing sensitive data. These issues are not fully solved in current literature, positioning our contribution as a step forward but not the final solution

7.2 Opportunities for Future Work

Future research can be expanded in the following directions:

- **Real-world Federated Deployment**: Implementing the system across actual healthcare institutions with edge computing nodes to assess system latency, model drift, and node failures in practice.
- **Dynamic Differential Privacy Integration**: Incorporating adaptive privacy budgets that adjust ε and noise multipliers based on the training phase, data sensitivity, or per-client contribution.
- **Multimodal and Multi-task FL**: Extending the current work to include image data (e.g., radiology scans), wearable sensor signals, or multi-task learning settings (Sun et al., 2020).
- **Privacy-Utility Optimization**: Introducing reinforcement learning or optimization-driven approaches to dynamically balance privacy loss with model performance.
- **Explain ability in FL**: Embedding explainable AI (XAI) modules in the federated pipeline to enhance trust in clinical applications.

We aim to pursue these directions to further enhance the security, scalability, and clinical reliability of FL systems for medical data environments. By framing these as open computing research challenges, our work contributes not just to healthcare AI but also to the broader study of how federated, privacy-preserving, and cryptographically resilient systems can be deployed in real-world distributed environments.

8. CONCLUSION

In this study, we presented a novel privacy-preserving FL framework for secure healthcare data analysis by integrating (DP) and decentralized encryption key generation mechanisms. Recognizing the sensitivity of electronic health records (EHRs), our approach ensured that model training occurs across distributed institutions without compromising data confidentiality. Through the incorporation of DP techniques, we safeguarded against reconstruction and inference attacks, while the decentralized key management further strengthened trust boundaries between clients and the central aggregator.

The proposed system was evaluated using a processed subset of the MIMIC-III clinical dataset, and its performance was assessed through a range of metrics including accuracy, client-wise variability, convergence, privacy budgets (ε, δ), and noise sensitivity. Notably, our results demonstrate that the FL model augmented with (FL+DP) outperformed standard FL in terms of both utility and privacy, especially when optimized with appropriate noise parameters.

This conclusion directly answers the questions raised in the introduction:

- Can FL+DP secure sensitive healthcare data without degrading performance? → Yes, as demonstrated by achieving 96.1% accuracy under ε = 1.9.
- Can decentralized key generation strengthen trust and remove single points of failure? → Yes, our design shows that cryptographic resilience can be achieved in parallel with federated training.
- Does privacy necessarily reduce utility? → No, our findings indicate that carefully tuned privacy can stabilize learning and even improve generalization in heterogeneous environments. These answers confirm that our hypothesis privacy and security can coexist without sacrificing model utility holds true in experimental validation.

Unlike prior works that either optimized accuracy (Shukla et al., 2025) or improved privacy trade-offs (Zheng et al., 2025), our contribution demonstrates novelty by unifying privacy preservation with decentralized cryptographic key generation in a single framework. This makes our work not just an incremental improvement but a step toward trustworthy, multi-institutional AI in healthcare. This paper shows that future privacy-preserving computing must be holistic: protecting both the learning process and the underlying cryptographic infrastructure. By addressing privacy, scalability, and key management together, our framework lays the groundwork for a new class of federated systems that can be trusted in sensitive, compliance-driven domains like healthcare.

REFERENCES:

[1] Shukla, V., Menon, A., & Iyer, P. (2025). *FL + DP for Breast Cancer Diagnosis: Scalable Privacy Frameworks*. Nature Scientific Reports.

[2] Zheng, Y., Rao, H., & Kim, J. (2025). *Sensitivity-aware differential privacy for medical imaging using adaptive noise mechanisms*. MDPI Sensors, 25(4), 5632–5644.

[3] Parampottupadam, G., Batra, A., & Rehman, M. H. (2025). *Compliance-aware differential privacy in federated healthcare systems*. arXiv preprint arXiv:2504.09876.

[4] Wang, R., Liu, M., & Gupta, D. (2024). *Federated transfer learning with differential privacy for mental health monitoring*. arXiv preprint arXiv:2401.07654.

[5] JMIR AI. (2025). *Federated Learning at Scale: The Personal Health Train Architecture for Cross-border Collaboration*. JMIR AI, 2(1), e42350.

[6] Ahmad, S et al. (2023). Hybrid cryptographic approach to enhance the mode of key management system in cloud environment. *The Journal of Supercomputing, 79*(7), 7377–7413.

[7] Adaramola, O. O. (2023). Blockchain securities issues: Decentralized identity system with key management perspective.

[8] Abaoud, M., Almuqrin, M. A., & Khan, M. F. (2023). Advancing federated learning through novel mechanism for privacy preservation in healthcare applications. *IEEE Access, 11*, 83562–83579.

[9] Punhani, A. (2024). A Perspective to Cloud Computing in Healthcare Sector. In *2024 2nd International Conference on Disruptive Technologies (ICDT)* (pp. 811–817). IEEE.

[10] Himanshu, & Punhani, A. (2024, May). Optimal Key Generation using Support Vector Machine for Health Records. In *2024 International Conference on Emerging*

Innovations and Advanced Computing (INNOCOMP) (pp. 673–678). IEEE.

[11] Wang, T., et al (2023). Applications of federated learning in mobile health: Scoping review. *Journal of Medical Internet Research, 25*, e43006.

[12] Singh, P. et al. (2023, December). Heart disease diagnosis using machine learning classifiers. In *International Advanced Computing Conference* (pp. 188–196). Springer Nature Switzerland.

[13] Khan, S.,et al.(2022). An optimized artificial intelligence system using IoT biosensors networking for healthcare problems. *Computational Intelligence and Neuroscience, 2022*(1), 2206573.

[14] Singh, R. S. et al. (2022). A secure and stable humanoid healthcare information processing and supervisory method with IoT-based sensor network. *Journal of Sensors, 2022*(1), 8568540.

[15] Zhong, C et al. (2024). Federated learning-guided intrusion detection and neural key exchange for safeguarding patient data on the internet of medical things. *International Journal of Machine Learning and Cybernetics*, 1–31.

[16] El Ouadrhiri, A. et al. (2022). Differential privacy for deep and federated learning: A survey. *IEEE Access, 10*, 22359–22380.

[17] Islam, S., et al. (2024). Decentralized vs. centralized database solutions in blockchain: Advantages, challenges, and use cases. *Global Mainstream Journal of Innovation, Engineering & Emerging Technology, 3*(4), 58–68.

[18] Du, J., et al. (2021). Dynamic differential-privacy preserving SGD. *arXiv preprint arXiv:2111.00173*.

[19] Xu, J., et al. (2021). Federated learning for healthcare informatics. *Journal of Healthcare Informatics Research, 5*, 1–19.

[20] Wei, K., et al. (2020). Federated learning with differential privacy: Algorithms and performance analysis. *IEEE Transactions on Information Forensics and Security, 15*, 3454–3469.

[21] Sun, W., et al. (2020). Adaptive federated learning and digital twin for industrial internet of things. *IEEE Transactions on Industrial Informatics, 17*(8), 5605–5614.

[22] Kuzminykh, I., et al. (2020, October). Analysis of encryption key management systems: Strengths, weaknesses, opportunities, threats. In *2020 IEEE International Conference on Problems of Infocommunications. Science and Technology (PIC S&T)* (pp. 515–520).

[23] Choudhury, O., et al. (2019). Differential privacy-enabled federated learning for sensitive health data. *arXiv preprint arXiv:1910.02578*.

[24] Zhao, J., et al. (2019). Differential privacy preservation in deep learning: Challenges, opportunities and solutions. *IEEE Access, 7*, 48901–48911.

[25] Habeeb, S. et al (2018). An integrated cloud based healthcare system. In *2018 Fifth International Conference on Internet of Things: Systems, Management and Security* (pp. 268–273).

[26] Edemekong, P. F., et al. (2018). Health insurance portability and accountability act.

[27] Geyer, R. C et al. (2017). Differentially private federated learning: A client-level perspective. *arXiv preprint arXiv:1712.07557*.

[28] McMahan, B., et al. (2017). Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics* (pp. 1273–1282). PMLR.

[29] Tawakol, A. M. (2016). Using Shamir's secret sharing scheme and symmetric key encryption to achieve data privacy in databases.

[30] Sultan, N. (2014). Making use of cloud computing for healthcare provision: Opportunities and challenges. *International Journal of Information Management, 34*(2), 177–184.

[31] Agarwal, R., et al. (2017). A review of PHR, EMR and EHR integration: Personalized healthcare and public health. *JIMS8I-International Journal of Information Communication and Computing Technology, 5*(2), 310–317.

[32] Bello, J. L. et al. (2025). Predictive classification and regression models for bioimpedance vector analysis: Insights from a southern Cuban cohort. *management*, *1*, 12.

[33] Chowdhury, T. N., et al. (2025). A Hybrid Data-Driven Approach For Analyzing And Predicting Inpatient Length Of Stay In Health Centre. *arXiv preprint arXiv:2501.18535*.

[34] Shukla, S., et al (2025). Federated learning with differential privacy for breast cancer diagnosis enabling secure data sharing and

ISSN: 1992-8645 www.jatit.org E-ISSN: 1817-3195

model integrity. *Scientific Reports*, *15*(1), 13061.

[35] Sharma, D. K., et al. (2023, December). A Study of the Unbalanced Image Dataset for Classification Problem. In *2023 12th International Conference on System Modeling & Advancement in Research Trends (SMART)* (pp. 239-243). IEEE.

[36] Ali, A., et al. (2025). Health-FedNet: A Privacy-Preserving Federated Learning Framework for Scalable and Secure Healthcare Analytics. *Results in Engineering*, 106484.

[37] Li, J., et al. (2025). Fast-CFLB: a privacy-preserving data sharing system for Internet of Vehicles using ternary federated learning and blockchain. *Cluster Computing*, *28*(8), 499.

[38] Gupta, M., et al. (2024). Security challenges and solutions using healthcare cloud computing. In *Pioneering Smart Healthcare 5.0 with IoT, Federated Learning, and Cloud Security* (pp. 198-219). IGI Global Scientific Publishing.

[39] Ribeiro, B. R. G. (2024). *Aprendizagem federada para comunidades de agentes que permita a mobilidade dinâmica em ambientes de proteção de privacidade* (Master's thesis, Instituto Politecnico do Porto (Portugal)).

[40] Ali, A. et al. (2025). Securing electronic health records using blockchain-enabled federated learning for IoT-based smart healthcare. *Clinical eHealth*.

[41] Atitallah, S. B., et al. (2023). Revolutionizing disease diagnosis: A microservices-based architecture for privacy-preserving and efficient IoT data analytics using federated learning. *Procedia Computer Science*, *225*, 3322-3331.

[42] Rizwan, A., et al. (2023). Intelligent digital twin for federated learning in AIoT networks. *Internet of Things*, *22*, 100698.

[43] Majeed, A., et al. (2025). A Comprehensive Analysis of Privacy-Preserving Solutions Developed for IoT-Based Systems and Applications. *Electronics*, *14*(11), 2106.

[44] Ghanta, S., et al. (2025). Enhancing privacy-preserving brain tumor classification with adaptive reputation-aware federated learning and homomorphic encryption. *PeerJ Computer Science*, *11*, e3165.

[45] Tom, A. K et al. (2025). Survey of Federated Learning for Cyber Threat Intelligence in Industrial IoT: Techniques, Applications and Deployment Models. *Future Internet*, *17*(9), 409.

[46] Mathew, C., et al. (2024). Improved Data Privacy with Differential Privacy in Federated Learning. *J. Wirel. Mob. Networks Ubiquitous Comput. Dependable Appl.*, *15*(3), 262-280.